

**SYSTEM FOR TRANSMITTING VIDEO IMAGES OVER A
COMPUTER NETWORK TO A REMOTE RECEIVER**

Related Applications

5 This application claims priority under 35 U.S.C. § 119(e) of the co-pending U.S. provisional application Serial Number 60/085,818 filed on May 18, 1998 and entitled "APPARATUS FOR TRANSMITTING LIVE VIDEO IMAGES OVER A COMPUTER NETWORK TO MULTIPLE REMOTE RECEIVERS." The provisional application Serial Number 60/085,818 filed on May 18, 1998 and entitled "APPARATUS FOR TRANSMITTING LIVE VIDEO IMAGES OVER A COMPUTER NETWORK TO MULTIPLE REMOTE RECEIVERS" is also hereby incorporated by reference.

Field of the Invention

 This invention relates to the field of communications systems. More particularly, this invention relates to the field of video communications systems.

Background of the Invention

10 In the last decade, there have been tremendous advances in medical devices which have greatly improved the ability to diagnose and treat patients. Ultrasounds, sonograms, echocardiograms, and angioplastigrams are just a few modern tools developed to accurately
20 diagnose patients with coronary problems, kidney stones, tumors, and other diseases without conducting risky and expensive exploratory surgeries. These tools are especially useful because they have the capability of being more accurate than exploratory surgeries and do not pose an additional risk to patients.

25 Given the benefits of ultrasounds, sonograms, echocardiograms, and angioplastigrams, these tools are in widespread use in many hospitals, clinics, testing facilities, and individual doctors' offices. Many doctors primarily base their diagnosis on the results from ultrasounds,

sonograms, echocardiograms, and angioplastigrams. While these tools allow doctors to make their diagnosis without costly, risky, and time consuming exploratory surgeries, an error in administering an ultrasound, sonogram, echocardiogram, and angioplastigram can lead to a wrong diagnosis. A wrong diagnosis can be catastrophic for the patient. By receiving an incorrect diagnosis, the patient can potentially fail to receive needed medical treatment and/or be unnecessarily treated. Whether needed medical treatment is withheld or unnecessary medical treatment is given due to an erroneous test result from an ultrasound, sonogram, echocardiogram, or angioplastigram, the patient unnecessarily suffers.

While ultrasounds, sonograms, echocardiograms, and angioplastigrams are extremely useful tools to diagnose ailments in patients, any of these tools administered in an imprecise manner or in a wrong location will most likely produce a wrong result. This wrong result typically leads to the wrong diagnosis. Learning proper techniques and procedures in order to produce a correct result from an ultrasound, sonogram, echocardiogram, or angioplastigram requires extensive specialized training and many years of medical training. People who possess such specialized knowledge in administering ultrasounds, sonograms, echocardiograms, and angioplastigrams are in short supply and only administer a fraction of these tests which are performed each year. Instead, technicians with limited medical knowledge and limited training typically administer these tests. By not properly administering these tests, the results are often times inaccurate and lead to the wrong diagnosis. Furthermore, the tests are typically performed and later reviewed by the doctor after the patient has left the technician's office.

In order to achieve a higher accuracy rate, close supervision by a specially trained person is needed while a technician administers any one of these tests. However, having such a specially trained person at each of these tests while they are being administered is typically impractical and would result in much higher medical costs.

Summary of the Invention

A method of and apparatus for transmitting video images preferably allows a specially trained individual to remotely supervise, instruct, and observe administration of medical tests conducted at remote locations. This apparatus preferably includes a source device, a transmitting device, and at least one remote receiving device. Preferably, the transmitting device and the remote receiving device communicate over a network such as the Internet Protocol network. Alternatively, the transmitting device and the receiving device communicate over any appropriate data network. The transmitting device transmits the video images to the remote receiving device either for live display through the source device or for pre-recorded display through a video recorder device. The remote receiving device is also capable of communicating with the transmitting device while simultaneously receiving video images. The source device is preferably a medical test device such as an ultrasound, a sonogram, an echocardiogram, an angioplastigram, and the like. This medical test device preferably generates video images for the transmitting device. The transmitting device captures the video images in real-time from the source device and compresses these video images utilizing a compression algorithm prior to transmitting data representing the video images to the remote receiving device. Remote users utilizing the remote receiving devices are capable of remotely controlling a number of parameters relating to the source device and the transmitting device. Such parameters include image quality, storage of the video images on the transmitting device, manipulating and controlling the source device, and the like.

Brief Description of the Drawings

Figure 1 illustrates a block diagram of a preferred embodiment of the present invention.

Figure 2 illustrates a data flow diagram of the preferred embodiment of the present invention.

Figure 3A illustrates software code utilized during a compression process of the present invention.

Figure 3B illustrates a look-up table representing the software code utilized during the compression process of the present invention.

5 Figure 4A illustrates a flow chart showing the steps involved in the compression process within a compressor of the preferred embodiment.

Figure 4B illustrates a representative video image and a corresponding stream of pixels.

Figure 5A illustrates a data structure of the present invention.

Figure 5B illustrates the data structure configured to transmit a repeat command for the preferred embodiment.

Figure 5C illustrates the data structure for the preferred embodiment configured to transmit a line number which represents a pixel illumination intensity level.

Figure 6 illustrates a sample data stream representing video pixels and a corresponding compressed data stream.

Figure 7 illustrates software code utilized during a decompression process of the present invention.

Figure 8A illustrates a flow chart showing the steps for transmitting a stream of video images in real-time.

20 Figure 8B illustrates a flow chart showing the steps for transmitting a pre-recorded stream of video images.

Figure 9 illustrates a flow chart showing the steps involved during the decompression process of the present invention.

25 Figure 10 illustrates an uncompressed data stream, a corresponding compressed data stream, and a corresponding converted data stream of the present invention.

Detailed Description of the Invention

Figure 1 illustrates a video system 100 according to the present invention for transmitting video images from one location to another. The video system 100 preferably includes a video source 101, a video cassette recorder 102, a transmitter 103, a recorded video device 104, a computer network 105, a plurality of receivers 106, and data links 110, 115, 120, and 125. Preferably, the video source 101 includes the video cassette recorder 102 and is coupled to the transmitter 103 via the data link 110. The data link 110 is preferably a Super-Video (S-Video) connection. The transmitter 103 is also preferably coupled to the recorded video device 104 and the computer network 105 via the data links 115 and 120, respectively.

Preferably, the plurality of receivers 106 are coupled to the computer network 105 via the data links 125. Each of the plurality of receivers 106 are preferably a computer system having a display, central processing unit, and input device. The data links 125 preferably link each of the plurality of receivers 106 to the computer network 105. The data links 125 include any appropriate connection to the computer network 105 including T1 communication lines, DSL links, cellular links, microwave transmission, land lines, twisted pair cable, and the like. The video system 100 shown in Figure 1 is merely illustrative and is only meant to show the preferred embodiment of the present invention. In alternate embodiments, additional transmitters, video sources, and receivers could be included without departing from the spirit and scope of the video system 100. Additionally, in an alternate embodiment, the transmitter 103 is included within the computer network 105 and functions as a server within the computer network 105.

The video source 101 preferably provides the video system 100 with at least one video image. The video source 101 is capable of providing either a real-time video image or a pre-recorded video image. For example, to provide a real-time video image, the video source 101 preferably includes a real-time input device 130. This real-time input device 130 is preferably a medical measurement device such as an ultrasound, sonogram, echocardiogram,

angioplastigram, and the like. Alternatively, this real-time input device 130 could be any other appropriate image capturing device including a video camera and a still camera. The pre-recorded video image is preferably provided by the video cassette recorder 102. Preferably, the video cassette recorder 102 is configured to record the real-time video images produced by the real-time input device 130 and play these pre-recorded video images at a later time. In addition to recording real-time video images and re-playing them, the video cassette recorder 102 is also preferably configured to accept and play a pre-recorded video cassette tape. The video source 101 is preferably configured to transfer the video image to the transmitter 103 via the data link 110.

The recorded video device 104 is preferably coupled to the transmitter 103 via the data link 115. Preferably, the recorded video device 104 stores video images received by the transmitter 103 for playback at a later time. The recorded video device 104 allows the transmitter 103 to distribute these video images to the plurality of receivers 106 at a later time. In addition, the recorded video device 104 also preferably serves as a mass storage device to store data that is unrelated to the video images.

The transmitter 103 preferably controls the flow of video images from both the video source 101 and the recorded video component 104 over the computer network 105 to any number of the plurality of receivers 106. Preferably, the transmitter 103 compresses the video images prior to transmission to one of the plurality of receivers 106, as will be described in detail below. Further, the transmitter 103 preferably monitors and selectively establishes connections with the computer network 105 over the data link 120.

In the video system 100, the computer network 105 is preferably an Internet Protocol network. In alternate embodiments, the computer network 105 is any appropriate data network. The computer network 105 is configured to transmit information between the plurality of receivers 106 and the transmitter 103 via the data links 125 and 120, respectively.

The plurality of receivers 106 are preferably configured to selectively receive a stream of video images from the transmitter 103 via the data link 120, the computer network 105,

and the appropriate data link 125. For example, at least one of the plurality of receivers 106 is programmed to receive the stream of video images from the transmitter 103. Accordingly, only the selected ones of the plurality of receivers 106 are capable of receiving the stream of video images from the transmitter 103. In addition to receiving the stream of video images, the selected ones of the plurality of receivers 106 are also capable of transmitting instructions to the transmitter 103 via the data link 125, the computer network 105, and the data link 120.

Figure 2 illustrates a data path diagram of the preferred embodiment of the present invention. Figure 2 shows a video system 200 which is similar to the video system 100 shown in Figure 1. The video system 200 preferably includes a transmitter 201, a video source 203, and a plurality of receivers 206. The video system 200 shown in Figure 2 is merely illustrative and is meant to show the preferred embodiment of the present invention. In alternate embodiments, additional components such as transmitters, video sources, and receivers are included without departing from the spirit and scope of the video system 200.

Preferably, the video source 203 is coupled to the transmitter 201 via a data link 250. Upon direction from the transmitter 201, the video source 203 is preferably configured to supply the transmitter 201, through a video image capture device 202, with a stream of video images through the data link 250.

The transmitter 201 preferably includes the video image capture device 202, a video server 212, a video controller 209, a listener device 213, a recorded video transmitter 215, and a plurality of socket handlers 214. The video image capture device 202 also preferably includes a plurality of video settings 211 configured by the user. Preferably, the video image capture device 202 receives a stream of video images from the video source 203 and then transmits this stream of video images to the video server 212 via a data link 251. The plurality of video settings 211 preferably allow adjustments to be made for modifying the stream of video images received by the video server 212. Examples of adjustments included within the plurality of video settings 211 include brightness, contrast, hue, and the like.

The video server 212 preferably includes a compressor 204 and a buffer 223. As the stream of video images are received by the video server 212, the compressor 204 is configured to compress the stream of video images thereby creating a compressed stream of video images. As this compressed stream of video images is generated, the compressor 204 transmits each data block into the buffer 223. Once the buffer 223 holds the compressed stream of video images having a predetermined number of data blocks, the compressed stream of video images is transmitted to one or more of the plurality of receivers 206. The compressor 204 preferably utilizes a lossless compression algorithm to form the compressed stream of video images, as will be discussed in detail below. The compressor 204 preferably includes a buffer 222 for use with the compression algorithm. In an alternate embodiment, the compressor 204 utilizes a lossy algorithmic system to compress the flow of video images.

The video recorder 210 is capable of storing the stream of video images received by the transmitter 201 for transmission to one or more of the plurality of receivers 206 at a later time. Preferably, the stream of video images is compressed by the compressor 204 before being stored by the video recorder 210.

In order to transmit the compressed stream of video images in real-time, the transmitter preferably transmits the compressed stream of video images through the listener device 213. The listener device 213 is preferably configured to couple to the video server 212 via a data link 252. Preferably, the listener device 213 is also coupled to the plurality of socket handlers 214 via the data links 253 and monitors the plurality of socket handlers 214 for any connection requests. Upon receiving a connection from appropriate ones of the plurality of receivers 206 through a socket handler 214, the listener device 213 preferably informs the video server 212 via the data link 252. In order to transmit the stream of video images to the appropriate ones of the plurality of receivers 206, one of the plurality of socket handlers 214 couples to each of the appropriate ones of the plurality of receivers 206. The connection(s) between the plurality of socket handlers 214 and the appropriate ones of the

plurality of receivers 206 is (are) preferably formed through the computer network 105 (Figure 1).

In order to transmit the stream of video images at a later time, the video recorder 210 preferably stores the stream of video images. The video recorder 210 preferably includes an edit list 211 and is coupled to the video server 212 through a data link 256. The video recorder 210 is also coupled to a recorded video transmitter 215 through a data link 257. The video recorder 210 is preferably configured to control the initiation and termination of storing the stream of video images in response to instructions received by the video controller 209. The recorded video device 208 is preferably a storage device coupled to the video recorder 210 and configured to store the stream of video images. Thus, the recorded video device 208 allows the video system 200 to save the stream of video images originating from the video source 203 and allows the video system 200 to transmit this saved stream of video images to appropriate ones of the plurality of receivers 206 at a later time. The recorded video device 208 is preferably coupled to the recorded video transmitter 215 and configured to transmit the saved stream of video images from the transmitter 201 to the appropriate ones of the plurality of receivers 206 over the appropriate recorded video pipe(s) 216.

The plurality of receivers 206 preferably reside in a remote location relative to the transmitter 201. Preferably, the plurality of receivers 206 selectively receive the flow of video images from the transmitter 201 and also selectively respond to the transmitter 201 with instructions.

Each of the plurality of receivers 206 preferably includes a video controller 207, a video client 217, and a video play device 219. The video controller 207 preferably communicates with the video controller 209 of the transmitter 201 via a data link 220. Preferably, the video controller 207 relays information regarding the frame size, frame rate, compression algorithm, and other parameters being transmitted to the video controller 207 via the data link 220. Thus, a user interfacing with one of the plurality of receivers 206 is able to modify the frame size, frame rate, compression algorithm, and other parameters of the

incoming stream of video images to one of the plurality of receivers 206. Since the plurality of receivers 206 and the transmitter 201 are preferably located in remote locations, by interfacing with the video controller 207, the user is able to remotely control video parameters such as frame size, frame rate, compression algorithm, and the like which are included within the video settings 211 at the transmitter 201.

When receiving the compressed stream of video images in real-time from the video server 212 in the transmitter 201, the video client 217 in the receiver 206 preferably receives the compressed stream of video images. The video client 217 preferably includes a decompressor 218 which is configured to decompress the compressed stream of video images to form a representation of the original, uncompressed stream of video images. After the compressed stream of video images is processed by the decompressor 218, the resulting stream of video images is ready to be displayed. The decompressor 218 preferably includes a buffer 221 which is utilized with the decompression process.

When receiving the stored stream of video data at a later time from the recorded video device 208 in the transmitter 201, the video play device 219 preferably receives the stored stream of video data and allows the representative stream of video images to be displayed. Before being displayed, the stored stream of video data is decompressed by the decompressor 218 in order to form a representation of the original, uncompressed stream of video images.

Various procedures for monitoring the video data that is received by the plurality of receivers 206 for errors is apparent to those skilled in the art. Such errors can include faulty compression, faulty decompression, missing video data, delayed video data, and the like. Further, it is also apparent to those skilled in the art to alert and notify users of the appropriate plurality of receivers 206, the transmitter 201, and the source device 203 when any of these errors occur. In order to avoid unnecessarily complicating the discussion of the video system 200, specific details of the error detection and notification are not discussed.

In operation, the transmitter 201 acts as a server that is connected to an appropriate data network. Preferably, each of the plurality of receivers 206 individually acts as a stand-

alone computer system connected to the data network. The transmitter 201 selectively enables a data stream of video images to be transmitted to an appropriate one or more of the plurality of receivers 206. In order for a particular receiver 206 to receive the data stream of video images from the transmitter 201, the receiver 206 logs onto the computer network 105 (Figure 1) Preferably, the computer network 105 is the Internet Protocol network. Alternatively, the computer network 105 is any appropriate data network. Typically, in the preferred embodiment, this log on is accomplished by connecting through an Internet service provider. A connection between the transmitter 201 and the particular receiver 206 is preferably established through the computer network 105 (Figure 1). The particular receiver 206 preferably communicates with the transmitter 201 over the computer network 105 and furnishes a user identification, a password, or another form of identification and verification. Once the transmitter 201 identifies the particular receiver 206 as an approved user, the transmitter 201 allows the data stream of video images to be transmitted to the particular receiver 206. The transmitter 201 is capable of simultaneously transmitting the data stream of video images to multiple receivers 206.

Figure 8A illustrates a flow chart showing the steps involved when transmitting a stream of video images in real-time from the transmitter 201 (Figure 2) to one or more of the plurality of receivers 206. The steps 800-825 preferably occur within the transmitter 201 (Figure 2). The steps 830-840 preferably occur within one of the plurality of receivers 206 (Figure 2). The process of transmitting the stream of video images from the transmitter 201 to one of the plurality of receivers 206 (Figure 2) begins at the step 800. Next, the stream of video images from the video source 203 are captured in the video image capture device 202 (Figure 2) in the step 805. In the step 810, the stream of video images, captured by the video image capture device 202, is compressed by the compressor 204 (Figure 2) within the video server 212 (Figure 2). Next, in the step 815, a connection between one of the plurality of socket handlers 214 (Figure 2) and one of the plurality of receivers 206 (Figure 2) is initiated. In the step 820, the connection between the transmitter 201 (Figure 2) and one of the plurality

of receivers 206 (Figure 2) is confirmed by the listener device 213 (Figure 2). Next, the compressed stream of video images is transmitted to an appropriate one or more of the plurality of receivers 206 (Figure 2) in the step 825.

5 In the step 830, the appropriate one or more of the plurality of receivers 206 (Figure 2) receives the compressed stream of video images from the transmitter 201. Next in the step 835, the compressed stream of video images is decompressed by the decompressor 218 (Figure 2). Finally, the stream of video images is displayed for the user by one of the plurality of receivers 206 (Figure 2) in the step 840.

Figure 8B illustrates a flow chart showing the steps involved when transmitting a stream of pre-recorded video images from the transmitter 201 to one of the plurality of receivers 206. The steps 850-870 preferably occur within the transmitter 201 (Figure 2). The steps 875-885 preferably occur within one of the plurality of receivers 206 (Figure 2). The process of transmitting the pre-recorded stream of video images to one of the plurality of receivers 206 (Figure 2) begins at the step 850. Next, the stream of video images are captured in the video image capture device 202 (Figure 2) in the step 855. In the step 860, the stream of video images are then compressed by the compressor 204 (Figure 2) within the video server 212 (Figure 2). Next, in the step 865, the compressed stream of video images is stored within the recorded video device 208 (Figure 2), thus forming a pre-recorded and compressed stream of video images. This pre-recorded and compressed stream of video images is capable of being stored indefinitely and transmitted to one of the plurality of receivers 206 (Figure 2) at any time. Next, the step 870 represents the steps 815, 820, and 825 from Figure 8A, and is utilized to transmit the pre-recorded and compressed stream of video images to one of the plurality of receivers 206 (Figure 2). A resulting connection between one of the plurality of socket handlers 214 (Figure 2) and one of the plurality of receivers 206 (Figure 2) is initiated in the step 870. Additionally in the step 870, the connection between the transmitter 201 (Figure 2) and one of the plurality of receivers 206 (Figure 2) is confirmed by the listener device 213 (Figure 2). The pre-recorded and

compressed stream of video images is also transmitted to one or more of the plurality of receivers 206 (Figure 2) in the step 870.

5 In the step 875, the appropriate one or more of the plurality of receivers 206 (Figure 2) receives the pre-recorded and compressed stream of video images. Next, in the step 880, the pre-recorded and compressed stream of video images is decompressed by the decompressor 218 (Figure 2). The stream of video images is then displayed to the user by one of the plurality of receivers 206 (Figure 2) in the step 885.

6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203

This compression process is preferably optimized to compress data representing a stream of video images which originates from the video source 203 (Figure 2) and is received by the transmitter 201 (Figure 2). In practice, this data representing the stream of video images is transmitted in terms of a stream of pixel data. A predetermined number of pixels represent each video image. Further, each pixel is represented by illumination intensity values relating to a red scale, a green scale, and a blue scale. Each of the red scale, green scale and blue scale have illumination intensity values which range from 0 to 255. For each pixel, the illumination intensity value of zero represents a fully off state, and the illumination intensity value of "255" represents a fully on state.

To achieve a gray scale or black and white image, each pixel within the black and white image has the same illumination intensity value for the red, green, and blue scales. In the preferred embodiment, the stream of video images are displayed as black and white images which are defined by a gray-scale having 256 shades of gray. This optimizes the compression of the video data and recognizes that full color is not necessary for good quality video images from the medical measurement devices utilized with the preferred embodiment of the present invention. Because only black and white images are utilized, the compression process preferably utilizes the intensity values for only the blue scale to represent each pixel. These illumination intensity values are modified within the compressor 204 (Figure 2) before being transmitted to one of the plurality of receivers 206 (Figure 2) or stored in the video recorder 210, as described above. Alternatively, as will be apparent to those skilled in the art, full color is achieved by separately compressing and transmitting the red, green, and blue values.

In the preferred embodiment, to achieve black and white video images, the intensity values for the red and green scales are neither compressed nor transmitted. To achieve black and white video images, it is sufficient to compress and transmit the blue scale value for each pixel. At a later time after transmission and decompression of the blue scale value for each pixel, to display each pixel in terms of a gray scale, the red scale and the green scale values

for a particular pixel are generated from the blue scale value. Alternate embodiments of the present invention are capable of utilizing either the green scale or the red scale value to represent each pixel. Further, alternate embodiments utilizing video images displayed in color compress and transmit the red scale, green scale, and blue scale value.

5 Figure 3B illustrates a lookup table 350. This look-up table 350 shows a logical representation of the compression process according to the compression lookup table 310 shown in Figure 3A, for illustrative purposes only. The lookup table 350 classifies an eight bit illumination intensity value for a pixel into an appropriate level within a reduced level index representing the five bit line number. There are preferably 32 levels within this reduced level index, from 0 to 31 which are represented by the rows 0 to 31 on the left of the table 350. Each line number corresponds with one of the levels within the reduced level index. The lookup table 350 also includes 10 columns which are represented by letters "A" through "J". The entries within columns "A" through "I" represent the illumination intensity value for the pixel and correspond to the storage locations within the lookup table 350. Each of the illumination intensity values are compressed into the line number of the row on which the illumination intensity value is found within the table 350. The entries within the column "J" represent an average illumination intensity level associated with each line number, which will be discussed below in relation to the decompression lookup table. This average illumination intensity level falls within a range of a lowest and highest illumination intensity value within the particular row.

10
15
20

As a further example of the pixel data compression technique of the present invention utilizing the lookup table 350 when provided with pixel data having an illumination intensity value of 167, the line number 20 is provided as the compressed value from the compression lookup table. Any pixel having an illumination intensity value between 162 and 169 corresponds to the line number 20 in the lookup table 350. Accordingly, for pixels having illumination intensity values between and including 162 and 169, the five bit line number 20

25

is provided as the compressed value, which is either stored by the recorded video device 208 or transmitted by the transmitter 201 to one or more of the receivers 206.

Figure 5A illustrates a data structure 500 having 8 bits of storage. An identification bit 510 is preferably a leading bit within the data structure 500. This identification bit 510 signals whether the particular data structure contains a line number representing the illumination intensity level or a repeat value representing a number of times to repeat an illumination intensity value of a prior pixel. The data structure 500 is used to carry both compressed line number values and the repeat value for compressed strings of similar pixels.

Figure 5B illustrates a data structure 525 used to transmit the repeat value, which has a specific configuration of the data structure 500 (Figure 5A). To signal that this data structure 525 is transmitting a repeat value, the identification bit 510 includes a value corresponding to a logical one. The number of times to repeat is preferably stored in the seven remaining bits 530. By storing a logical one in the identification bit 510, the decompressor 218 (Figure 2) is instructed while decoding to repeat the line number of the previous pixel a number of times corresponding to the seven bit repeat value. In this preferred embodiment, the repeat counter value is limited to a value of 127 which is the maximum number capable of being expressed by seven bits. Alternatively, the repeat counter value can be represented by any appropriate number of bits.

Figure 5C illustrates a data structure 550 used to transmit a line number, which has a specific configuration of the data structure 500 (Figure 5A). To signal that this data structure 550 is transmitting a compressed line number, representing an illumination intensity value of a pixel, the identification bit 510 includes a value corresponding to a logical zero. The data structure 550 is configured to transmit the line number which represents the illumination intensity level of the pixel. Preferably, the bits 565 and 570 are unused. The bits 575-595 represent the five bit line number corresponding to the illumination intensity value from the compression lookup table 310 (Figure 3A). By setting the identification bit 510 to a logical zero, the decompressor 218 (Figure 2) recognizes that information held in the five bits 575-

595 represents the line number corresponding to the illumination intensity value of a pixel in the data stream.

Figure 4A shows a flow chart which illustrates the compression process utilized by the compressor 204 (Figure 2) when compressing a stream of video data. Figure 4B illustrates a representative video image 400 and a corresponding stream of pixel data 405 representing the video image 400. The pixel data is transmitted in an order representing pixels from left to right on each horizontal line, successively, from top to bottom of the video image. As an example, pixels "C" and "D" are considered consecutive pixels within the stream of pixels 405.

This compression process begins at the start step 402, clearing the buffer 222 (Figure 2) and resetting the repeat counter value to zero. At the step 404, an illumination intensity value representing a current pixel is received. Next, at the step 406, a current line number from the lookup table 310 (Figure 3A) is obtained for the pixel data corresponding to the current illumination intensity value for the pixel. At the step 408, it is determined whether the current line number for the pixel data is the same as the previous line number. The previous line number is preferably stored in the buffer 222 (Figure 2). If the previous line number is not stored in the buffer 222 (Figure 2), then the current line number and the previous line number cannot be the same. If the line number is the same as the previous line number, the repeat counter value is incremented by one, at the step 410. It is then determined whether the repeat counter value is equal to a value of 127, at the step 412. If the repeat counter value is equal to a value of 127, then, at the step 414, the repeat counter value is transmitted out of the compressor 204 (Figure 2) and into the buffer 223 (Figure 2) within a data structure that is similar to the data structure 525 (Figure 5B). Additionally in the step 414, the repeat counter value is reset to a value of zero after being transmitted in the data structure. If the repeat counter is not equal to the value of 127, the process then proceeds directly to the step 416.

Returning back to the step 408, if the current line number is not the same as the previous line number, then it is determined whether the repeat counter value is equal to a value of zero, in the step 420. If it is determined at the step 420, that the repeat counter value is not equal to the value of zero, then at the step 422, the repeat counter value is transmitted out of the compressor 204 (Figure 2) and into the buffer 223 (Figure 2) within a data structure that is similar to the data structure 525 (Figure 5B). Additionally, at the step 422, the repeat counter value is reset to a value of zero after being transmitted in the data structure. If it is determined at the step 420, that the repeat counter value is equal to the value of zero, or after the step 422 is completed, then the line number representing the current illumination intensity value is transmitted out of the compressor 204 (Figure 2) and into the buffer 223 (Figure 2), at the step 424, within a data structure that is similar to the data structure 550 (Figure 5C). Additionally, after the current line number is transmitted, the current line number is stored in the buffer 222 (Figure 2) as the previous line number, at the step 424. After the step 424 is completed, the process proceeds to the step 416.

At the step 416, it is determined whether there is any additional pixel data corresponding to additional pixels. If there is additional pixel data, then the compression process loops back to the step 404 to receive and process the data representing the next pixel. If there is no additional pixel data, then the process proceeds to the step 418. At the step 418, it is determined whether the repeat counter value is equal to a value of zero. If the repeat counter value is equal to the value of zero, then the process proceeds to the ending step 428. If the repeat counter value is not equal to the value of zero, then, at the step 426, the repeat counter value is transmitted out of the compressor 204 (Figure 2) and into the buffer 223 (Figure 2) within a data structure that is similar to the data structure 525 (Figure 5B). Additionally in the step 426, the repeat counter value is reset to a value of zero after being transmitted in the data structure. After the step 426, then the process proceeds to the ending step 428.

Figure 6 illustrates a sample uncompressed illumination intensity data stream 610 including data blocks 620, 622, 624, 626, 628, 630, and 632. Each block includes pixel data representing an illumination intensity value of a corresponding pixel in this uncompressed data stream 610. Preferably, this illumination intensity level is the blue scale value for the particular represented pixel. For example, after the step 406 (Figure 4A) of obtaining a line number value for each of the data blocks, the blocks 620-628 have a line number value of zero; the block 630 has a line number value of two; and the block 632 has a line number value of ten. A compressed illumination intensity data stream 640 includes data structures 650, 652, 654, and 656. The compressed data stream 640 represents the uncompressed data stream 610 with four data structures. Similar to the illumination intensity data structure 550 (Figure 5C), the data structures 650, 654, and 656 represent the illumination intensity value of the pixels associated with the data blocks 620, 630, and 632, respectively. A segment 651 of the data structure 650 contains a five bit line number having a value of zero. Similarly, the segments 655 and 657 contain five bit line numbers having values of two and ten, respectively. Similar to the repeat data structure 525 (Figure 5B), the data structure 652 represents the illumination intensities of the pixels associated with the data blocks 622, 624, 626, and 628. A segment 653 stores the seven bit repeat counter value of four which is the number of times the line number of the prior pixel 620 is repeated.

Figure 7 illustrates software code utilized to decompress a compressed stream of data. This software code includes a decompression lookup table 700 which is utilized within the decompressor 218 (Figure 2). The decompression lookup table 700 is indexed to provide an output average illumination intensity value corresponding to the received line number from the compression lookup table 310. This decompression lookup table 700 transforms the line number representing the illumination intensity for the stream of pixels which was previously processed by the compressor 204 (Figure 2) back into a converted illumination intensity data stream having thirty-two levels of illumination intensity. Similar to the compression lookup table 310 (Figure 3A), the decompression lookup table 700 utilizes thirty-two levels wherein

each level represents the particular line number. For each received line number, the decompression lookup table 700 provides an output average illumination intensity value for a red scale illumination intensity value 710, a green scale illumination intensity value 720, and a blue scale illumination intensity value 730. Preferably, these output average illumination intensity values are all equal, thereby providing a gray scale image.

Figure 9 illustrates a flow chart which shows the preferred decompression process utilized by the decompressor 218 (Figure 2) to decompress a compressed stream of data. This decompression process begins at a start step 900 and proceeds to the step 902. At the step 902, a stream of compressed data which was compressed by the compressor 204 (Figure 2) and includes data representing the illumination intensity of a plurality of pixels waits to be received. The stream of compressed data contains a plurality of data structures which resemble the data structure 500 (Figure 5A). At the step 902, the next data structure in the stream of compressed data is received as a present data structure. Next, at the step 904, the identification bit within the present data structure received by the step 902 is detected. At the step 906, it is determined if the identification bit which was detected at the step 904 has a value of logical zero or logical one. If the identification bit has a value of logical one, then the present data structure contains a repeat counter value and is decoded at the step 912. If the identification bit has a value of logical zero, then the present data structure contains a line number and is decoded at the step 908.

At the step 912, the repeat counter value is read from the present data structure. Recall that the repeat counter value stores the number of times to repeat the line number associated with the illumination intensity values of the prior pixel. Next, at the step 914, a particular number of pixels corresponding to a number stored as the repeat counter value, is generated with the illumination intensity values of the prior pixel. The illumination intensity value of the prior pixel is stored in the buffer 221 (Figure 2) within the decompressor 218 (Figure 2). For example, if the repeat counter value is five, then five pixels are generated with the illumination intensity values of the prior pixel at the step 914.

At the step 908, the line number is read from the present data structure. The line number corresponds to a row within the decompression lookup table 700 (Figure 7) which includes the illumination intensity values for the pixel. Next, at the step 910, a pixel is generated having illumination intensity values which correspond to the line number read from the step 908. Additionally, the illumination intensity values are also stored in the buffer 221 (Figure 2) within the decompressor 218 (Figure 2). For example, if the line number within the present data structure has a value of two, then according to the decompression lookup table 700 (Figure 7), the illumination intensity values for the red, green, and blue values of the pixel are sixteen.

After the illumination intensity values are determined at the step 910 or the step 914, it is determined, at the step 916, if there are additional data structures within the compressed stream of data currently being received. If there are additional data structures, then this process loops back to the step 902 where the next data structure is received, and the process begins again. If there are not additional data structures, then this process ends at the step 918.

The compression process as described above and illustrated in the flow chart shown in Figure 4A is embodied and executed within the compressor 204 (Figure 2) utilizing the compression lookup table 310 (Figure 3A). An uncompressed stream of data containing a plurality of eight bit illumination intensity values for a stream of pixels, each having 256 possible levels, is processed within the compressor 204 (Figure 2). Each illumination intensity value in the uncompressed stream of data is transformed by the compressor 204 (Figure 2) into a five bit line number having 32 possible levels. This line number represents the illumination intensity value having one of 32 possible levels for a corresponding pixel. In other words, each of the 32 line numbers represents a specific range of illumination intensity values.

By transforming the uncompressed eight bit illumination intensity value having 256 possible levels into the compressed five bit line number having 32 possible levels, some accuracy is lost in this transformation. However, because of inherent characteristics of the

human eye, this accuracy loss is not noticeable when viewing a resulting image composed of pixels having illumination intensity values represented by corresponding line numbers. In order to achieve additional compression, the compressor 204 (Figure 2) also stores the number of consecutive times a prior line number is repeated as a repeat counter. The compressor 204 (Figure 2) then replaces the repeated line number(s) with a single repeat data structure which contains the repeat counter. The compressor 204 (Figure 2) produces a compressed stream of data including line number data structures and repeat data structures, as appropriate.

The decompression process as described in detail above and illustrated in the flow chart shown in Figure 9 is embodied and executed within the decompressor 218 (Figure 2) which utilizes the decompression lookup table 700 (Figure 7). The compressed stream of data is processed by the decompressor 218 (Figure 2) to transform a combination of line numbers and repeat values into a decompressed stream of illumination intensity values corresponding to the original stream of pixels. When the decompressor 218 (Figure 2) receives a particular line number, the line number is converted into appropriate illumination intensity values for the corresponding pixel in terms of the red scale, green scale, and blue scale through the decompression lookup table 700 (Figure 7). The appropriate illumination intensity values are placed in the converted stream of illumination intensity values.

When receiving a particular repeat command from the compressed stream of data, the decompressor 218 (Figure 2) generates an appropriate number of illumination intensity values, representing a number of pixels, in response to the repeat counter, having the same illumination intensity values as the most recent illumination intensity value in the converted stream of illumination intensity values. Each of the appropriate number of illumination intensity values is placed in the converted stream of illumination intensity values. After the decompression process, the converted stream of illumination intensity values include a plurality of illumination intensity values which closely approximates the plurality of illumination intensity values within the uncompressed stream of data.

In Figure 10, sample data streams illustrating the compression and the decompression process of the present invention are shown. The sample data streams include an uncompressed data stream 1000, a compressed data stream 1020, and a decompressed data stream 1050. The uncompressed data stream 1000 includes seven pixel data blocks 1002 through 1014 wherein each of these pixel data blocks represents the illumination intensity value of the particular pixel. The compressed data stream 1020 includes four data blocks 1022-1028 which are generated by the compressor 204 (Figure 2) and represent the uncompressed data stream 1000. The decompressed data stream 1050 is generated from the decompressor 218 (Figure 2) and includes seven pixel data blocks 1052-1064 each representing the average illumination intensity value of the particular pixel.

In operation, the compressor 204 (Figure 2) receives the uncompressed data stream 1000. The pixel data blocks 1002, 1004, 1006, 1008, 1010, 1012, and 1014 store the illumination intensity values "22", "24", "21", "28", "27", "113", and "15", respectively. According to the step 404 (Figure 4A), the pixel data block 1002 is received. Next in the step 406 (Figure 4A), the current line number for the pixel data block 1002 has a value of three, corresponding to the value stored within the storage location in the lookup table 310, representing the illumination intensity value "22." Since the pixel data block 1002 is the first pixel data block within the uncompressed data stream 1000, the current line number is not the same as the previous line number, and the repeat counter value is equal to a value of zero. Accordingly, in the step 424 (Figure 4A), the current line number having the value of three is transmitted into the buffer 223 (Figure 2) and is represented as a data structure 1022 in the compressed data stream 1020 which is similar to the data structure 550 (Figure 5C). Further, the current line number is stored as the previous line number in the buffer 222 (Figure 2). Next, since the pixel data blocks 1004 through 1014 remain waiting to be processed, the process loops back to the step 404 (Figure 4A).

In the step 404 (Figure 4A), the pixel data block 1004 is received. Next in the step 406 (Figure 4A), the current line number for the pixel data block 1004 has the value of three,

corresponding to the value stored within the storage location in the lookup table 310, representing the illumination intensity value "24." In the step 408 (Figure 4A), the current line number value is determined to be the same as the previous line number value. Next, the repeat counter value is increased from zero to one, at the step 410 (Figure 4A). Since the repeat counter value is not equal to 127, the process proceeds to the step 416 (Figure 4A). Next, since the pixel data blocks 1006 through 1014 remain waiting to be processed, the process loops back to the step 404 (Figure 4A).

In the step 404 (Figure 4A), the pixel data block 1006 is received. Next in the step 406 (Figure 4A), the current line number for the pixel data block 1006 has the value of three, corresponding to the value stored within the storage location in the lookup table 310, representing the illumination intensity value "21." In the step 408 (Figure 4A), the current line number value is determined to be the same as the previous line number value. Next, the repeat counter value is increased from one to two, at the step 410 (Figure 4A). Since the repeat counter value is not equal to 127, the process proceeds to the step 416 (Figure 4A). Next, since the pixel data blocks 1008 through 1014 remain waiting to be processed, the process loops back to the step 404 (Figure 4A).

In the step 404 (Figure 4A), the pixel data block 1008 is received. Next in the step 406 (Figure 4A), the current line number for the pixel data block 1008 has the value of three, corresponding to the value stored within the storage location in the lookup table 310, representing the illumination intensity value "28." In the step 408 (Figure 4A), the current line number value is determined to be the same as the previous line number value. Next, the repeat counter value is increased from two to three, at the step 410 (Figure 4A). Since the repeat counter value is not equal to 127, the process proceeds to the step 416 (Figure 4A). Next, since the pixel data blocks 1010 through 1014 remain waiting to be processed, the process loops back to the step 404 (Figure 4A).

In the step 404 (Figure 4A), the pixel data block 1010 is received. Next in the step 406 (Figure 4A), the current line number for the pixel data block 1010 has the value of three,

corresponding to the value stored within the storage location in the lookup table 310, representing the illumination intensity value "27." In the step 408 (Figure 4A), the current line number value is determined to be the same as the previous line number value. Next, the repeat counter value is increased from three to four, at the step 410 (Figure 4A). Since the repeat counter value is not equal to 127, the process proceeds to the step 416 (Figure 4A). Next, since the pixel data blocks 1012 through 1014 remain waiting to be processed, the process loops back to the step 404 (Figure 4A).

In the step 404 (Figure 4A), the pixel data block 1012 is received. Next in the step 406 (Figure 4A), the current line number for the pixel data block 1012 has a value of fourteen, corresponding to the value stored within the storage location in the lookup table 310, representing the illumination intensity value "113." In the step 408 (Figure 4A), it is determined that the current line number value is not equal to the previous line number value. Accordingly, the process proceeds to the step 420 (Figure 4A). In the step 420 (Figure 4A), it is determined that the repeat counter value is not equal to zero. Accordingly, in the step 422 (Figure 4A), the repeat counter value of four is transmitted into the buffer 223 (Figure 2) and is represented as a data structure 1024 in the compressed data stream 1020 which is similar to the data structure 525 (Figure 5B). Next in the step 424 (Figure 4A), the current line number having the value of fourteen is transmitted into the buffer 223 (Figure 2) and is represented as a data structure 1026 in the compressed data stream 1020 which is similar to the data structure 550 (Figure 5C). Further, the current line number is stored as the previous line number in the buffer 222 (Figure 2). Further, the repeat counter value is reset back to the value of zero. Next, since the pixel data block 1014 remains waiting to be processed, the process loops back to the step 404.

In the step 404 (Figure 4A), the pixel data block 1014 is received. Next in the step 406 (Figure 4A), the current line number for the pixel data block 1014 has a value of two, corresponding to the value stored within the storage location in the lookup table 310, representing the illumination intensity value "15." In the step 408 (Figure 4A), it is

determined that the current line number value is not equal to the previous line number value. Accordingly, the process proceeds to the step 420 (Figure 4A). In the step 420 (Figure 4A), it is determined that the repeat counter value is equal to zero. Accordingly, in the step 424 (Figure 4A), the current line number having the value of two is transmitted into the buffer 223 (Figure 2) and is represented as a data structure 1028 in the compressed data stream 1020 which is similar to the data structure 550 (Figure 5C). Further, the current line number is stored as the previous line number in the buffer 222 (Figure 2). Since there are no more additional pixel data blocks waiting to be processed, and the repeat counter value is equal to zero, the process ends at the ending step 428 (Figure 4A).

The uncompressed data stream 1000 has been converted into the compressed data stream 1020. The compressed data stream 1020 includes four bytes of data instead of the seven bytes of data included within the uncompressed data stream 1000.

When the decompressor 218 (Figure 2) receives the compressed data stream 1020, it then generates the decompressed data stream 1050. In operation, the data structure 1022 is received as described in the step 902 (Figure 9). Next, the identification bit 1030 is determined to have a value of logical zero, in the steps 904 and 906 (Figure 9), representing that the data structure 1022 is carrying a line number. In response to this determination, the line number value of three is read from the segment 1032 in the step 908 (Figure 9).

According to the lookup table 700 (Figure 7), the line number value of three corresponds to an average illumination intensity value of twenty-four. The decompressor 218 (Figure 2) then generates the block 1052 which is encoded with the average illumination intensity value of twenty four and saves the illumination intensity value of twenty-four in the buffer 221 (Figure 2), at the step 910 (Figure 9). Next, it is determined that the data block 1024 is the next data structure in the step 916 (Figure 9). Accordingly, the process loops back to the step 902 (Figure 9).

In the step 902 (Figure 9), the data structure 1024 is received. The identification bit 1034 is determined to have a value of logical one, in the steps 904 and 906 (Figure 9),

representing that the data structure 1024 is carrying a repeat counter value. In response to this determination, a repeat counter value of four is read from the segment 1036, in the step 912 (Figure 9). The decompressor 218 (Figure 2) then reads the average illumination intensity value stored in the buffer 221 (Figure 2) and generates four blocks 1054, 1056, 1058, and 1060 each having the average illumination intensity values of twenty-four. Next, it is determined that the data structure 1026 is the next data structure in the step 916 (Figure 9). Accordingly, the process loops back to the step 902 (Figure 9).

In the step 902 (Figure 9), the data structure 1026 is received. The identification bit 1038 is determined to have a value of logical zero, in the steps 904 and 906 (Figure 9), representing that the data structure 1026 is carrying a line number. In response to this determination, the line number of fourteen is read from the segment 1040, in the step 908 (Figure 9). According to the lookup table 700 (Figure 7), the line number value of fourteen corresponds to an average illumination intensity value of "115." The decompressor 218 (Figure 2) then generates the block 1062 which is encoded with the average illumination intensity value of "115" and saves the illumination intensity value of "115" in the buffer 221 (Figure 2), at the step 910 (Figure 9). Next, it is determined that the data block 1028 is the next data structure in the step 916 (Figure 9). Accordingly, the process loops back to the step 902 (Figure 9).

In the step 902 (Figure 9), the data structure 1028 is received. The identification bit 1042 is determined to have a value of logical zero, in the steps 904 and 906 (Figure 9), representing that the data structure 1028 is carrying a line number. In response to this determination, the line number of two is read from the segment 1044, in the step 908 (Figure 9). According to the lookup table 700 (Figure 7), the line number value of two corresponds to an average illumination intensity value of "16." The decompressor 218 (Figure 2) then generates the block 1064 which is encoded with the illumination intensity value of sixteen and saves the illumination intensity value of sixteen in the buffer 221 (Figure 2), at the step 910

(Figure 9). Next, in the step 916 (Figure 9), it is determined that there is no additional data structure. Accordingly, the process ends at the ending step 918 (Figure 9).

In the preferred embodiment, only the blue scale illumination intensity relating to each pixel is compressed, transmitted, and finally decompressed. Because the preferred
5 embodiment utilizes black and white video images, the decoding table 700 decodes the average illumination value for the blue scale and automatically sets the same illumination intensity for both the red and green scales.

The above example of the preferred embodiment merely illustrates a sample operation of the present invention utilizing black and white video images. It is well within the scope of the present invention to utilize color video images.

The present invention has been described in terms of specific embodiments incorporating details to facilitate the understanding of the principles of construction and operation of the invention. Such reference herein to specific embodiments and details thereof is not intended to limit the scope of the claims appended hereto. It will be apparent to those skilled in the art that modifications may be made in the embodiment chosen for illustration without departing from the spirit and scope of the invention.